

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings of claims in the application:

**Listing of Claims:**

Claim 1. (currently amended) A method for operating an access control system to camouflage a secret so as to be accessible by an authorized user yet protected against unauthorized access, said method comprising the steps of:

- (a) representing in digital form a secret to be protected against unauthorized access;
  - (b) storing a plurality of computer-represented objects related to said secret;
    - (i) at least one of said objects being accessible by an authorized user as a password;
    - (ii) at least another of said objects being stored in a computer-readable wallet accessible to said access control system; and
  - (c) representing said secret as a function of said plurality of objects, using a composition function; and
  - (d) storing, in a computer-readable memory, said composition function:
    - (i) in a manner accessible to said access control system;
    - (ii) so as to be executable to generate a candidate secret using a user-inputted candidate password in conjunction with at least said another object stored in said wallet;
    - (iii) ~~said-generated candidate secret not regenerating said secret~~ generating a bogus secret configured to camouflage said secret if said candidate password is not said password; and
    - (iv) ~~said-generated candidate secret~~ regenerating said secret if said candidate password is said password;
- thereby protecting said secret against unauthorized access by camouflaging the secret from persons not having said password.

Claim 2. (original) The method of claim 1 further comprising effecting a multilevel camouflaging scheme by camouflaging said at least another object stored in said wallet.

Claim 3. (original) The method of claim 1 where:

- (a) said secret represents linkage information among nodes of a network;
- (b) said object accessible by an authorized user is a first graph representing at least a portion of said linkage information; and
- (c) said object stored in said wallet is a second graph representing at least a portion of said linkage information; and
- (d) said composition function accepts as operands at least said first and second graphs.

Claim 4. (original) The method of claim 1 where:

- (a) said secret represents at least one possible state of a system expressible as a Boolean logic function;
- (b) said object accessible by an authorized user is a first matrix representing at least one of said states of said Boolean function;
- (c) said object stored in said wallet is a second matrix representing at least one of said states of said Boolean function; and
- (d) said composition function accepts as operands at least said first and second matrices.

Claim 5. (original) The method of claim 1 where:

- (i) said secret is a private key of said user;
- (ii) said object accessible by said user is a PIN of said user;
- (iii) said another object stored in said wallet is a pseudo-valid PIN; and
- (iv) said candidate secret has the structural form of a private key.

Claim 6. (currently amended) A method for operating an access control system to release a secret camouflaged to be accessible to an authorized user yet protected against unauthorized access, said method comprising the steps of:

- (a) accessing a plurality of computer-represented objects related to a secret;
  - (i) at least one of said objects being accessible by an authorized user as a password;
  - (ii) at least another of said objects being stored in a computer-readable wallet accessible to said access control system; and
- (b) accessing a composition function representing said secret as a function of said plurality of objects;
- (c) receiving a candidate password inputted by a user;
- (d) generating a candidate secret for said user by executing said composition function using as operands thereto said candidate password in conjunction with at least said another object stored in said wallet;
  - (i) ~~said generated candidate secret not regenerating said secret~~ generating a bogus secret configured to camouflage said secret if said candidate password is not said password;
  - (ii) ~~said generated candidate secret~~ regenerating said secret if said candidate password is said password; and
- (e) outputting said candidate secret to said user of said access control system.

Claim 7. (currently amended) The method of claim 6 where in said step (d)(i) said ~~candidate~~ bogus secret is configured to deceive an unauthorized user into believing that said bogus ~~candidate~~ secret is said secret.

Claim 8. (original) The method of claim 6 where:

- (a) said secret represents linkage information among nodes of a network;
- (b) said object accessible by an authorized user is a first graph representing at least a portion of said linkage information;

- (c) said object stored in said wallet is a second graph representing at least a portion of said linkage information; and
- (d) said composition function accepts as operands at least said first and second graphs.

Claim 9. (original) The method of claim 6 where:

- (a) said secret represents at least one possible state of a system expressible as a Boolean logic function;
- (b) said object accessible by an authorized user is a first array representing at least one of said states of said Boolean function; and
- (c) said object stored in said wallet is a second array representing at least another of said states of said Boolean function; and
- (d) said composition function accepts as operands at least said first and second arrays.

Claim 10. (original) The method of claim 6 where:

- (i) said secret is a private key of said user;
- (ii) said object accessible by said user is a PIN of said user;
- (iii) said another object stored in said wallet is a pseudo-valid PIN; and
- (iv) said candidate secret has the structural form of a private key.

Claim 11. (currently amended) A method for operating an access control system to protect state information against unauthorized access, said method comprising the steps of:

- (a) obtaining state information represented in digital form;
- (b) deriving from said state information a first matrix;
- (c) storing said first matrix as a password usable by an authorized user;
- (d) deriving from said state information a second matrix;
- (e) storing said second matrix in a computer-readable wallet accessible to said access control system; and

(f) storing, in a computer-readable memory, a composition function executable to generate a candidate matrix using a user-inputted candidate password in conjunction with said second matrix;

(i) ~~said generated candidate state information not regenerating said matrix~~ generating a bogus matrix configured to camouflage said matrix if said candidate password is not said password; and

(ii) ~~said generated candidate state information~~ regenerating said matrix if said candidate password is said password;

thereby protecting said state information against unauthorized access by camouflaging said matrix from persons not having said password.

Claim 12. (original) The method of claim 11 further comprising effecting a multilevel access control scheme by camouflaging said second matrix.

Claim 13. (original) The method of claim 11 where said state information includes a graph representing the status of a network characterized by nodes and links among at least some of said nodes.

Claim 14. (original) The method of claim 13 used to protect an arbitrary secret representable in digital form, by representing said secret as interconnections among certain of said nodes, said interconnections being represented by values of said graph.

Claim 15. (original) The method of claim 14 where said graph, if expressed as a matrix in row- or column-major order, would comprise an array having values representing said secret.

Claim 16. (original) The method of claim 14 where said representing said secret includes padding said secret with sufficient bits to form a perfect square.

Claim 17. (original) The method of claim 13 where said graph is an undirected graph.

Claim 18. (original) The method of claim 13 where said graph is a directed graph.

Claim 19. (original) The method of claim 11 where said state information comprises at least an array including a plurality of output values of a Boolean function, each output value corresponding to a unique sequence of input values for operands of said Boolean function.

Claim 20. (original) The method of claim 19 where said state information further includes said sequences of input values corresponding to each of said output values.

Claim 21. (original) The method of claim 19 where:

- (a) said first and second matrices comprise arrays; and
- (b) said state information array represents output values of a Boolean function, said output values being ordered in a manner corresponding to a known but unstored hierarchy of sequences of possible input values to said Boolean function.

Claim 22. (original) The method of claim 19 used to protect an arbitrary secret expressed in digital form, by representing said secret as the values of said state information array.

Claim 23. (original) The method of claim 22 where said representing said secret includes padding said secret with sufficient bits to form an integer power of a base used in the computational logic of the access control system.

Claim 24. (currently amended) A method for operating an access control system to protect state information against unauthorized access, said method comprising the steps of:

- (a) retrieving a first matrix related to said state information from a computer-readable wallet accessible to said access control system;
- (b) accessing a composition function representing said state information as a function of said first matrix and a password stored as a second matrix;

- (c) receiving a candidate password inputted by a user;
- (d) generating candidate state information for said user by executing said composition function using as operands thereto said candidate password in conjunction with at least said first matrix stored in said wallet;
- (i) ~~said generated candidate state information not regenerating said state information~~ generating bogus state information to camouflage said state information if said candidate password is not said password;
- (ii) ~~said generated candidate state information~~ regenerating said state information if said candidate password is said password; and
- (e) outputting said candidate state information or bogus candidate state information to said user of said access control system.

Claim 25. (original) The method of claim 24 where at least one of said matrices is an array represented using row- or column-major ordering.

Claim 26. (original) The method of claim 24 where at least one of said matrices is stored on a smart card accessible to said user.

Claim 27. (original) The method of claim 24 where said state information includes a graph representing the status of a network characterized by nodes and links among at least some of said nodes.

Claim 28. (original) The method of claim 27 where said graph takes the form of an adjacency matrix.

Claim 29. (original) The method of claim 27 where said composition function includes graph addition.

Claim 30. (original) The method of claim 27 where said composition function includes a graph product operation.

Claim 31. (original) The method of claim 27 used to protect an arbitrary secret representable in digital form, by representing said secret as interconnections among certain of said nodes, said interconnections being represented by values of said graph.

Claim 32. (original) The method of claim 31 where said graph, if expressed as a matrix in row- or column-major order, would comprise an array having values equal to said secret.

Claim 33. (original) The method of claim 27 where said network includes elements of a physical network.

Claim 34. (original) The method of claim 27 where said network includes elements of a logical network.

Claim 35. (original) The method of claim 24 where said state information comprises at least an array including a plurality of output values of a Boolean function, each output value corresponding to a unique sequence of input values for operands of said Boolean function.

Claim 36. (original) The method of claim 35 where said state information further includes said sequences of input values corresponding to each of said output values.

Claim 37. (original) The method of claim 35 where:

- (a) said first and second matrices comprise arrays; and
- (b) said state information array represents output values of a Boolean function, said output values being ordered in a manner corresponding to a known but unstored hierarchy of sequences of possible input values to said Boolean function.

Claim 38. (original) The method of claim 37 used to protect an arbitrary secret expressed in digital form, by representing said secret as the values of said state information array.



Claim 39. (currently amended) A computer-readable medium containing logic instructions for operating an access control system to camouflage a secret so as to be accessible by an authorized user yet protected against unauthorized access, said logic instructions when executed:

- (a) representing in digital form a secret to be protected against unauthorized access;
  - (b) storing a plurality of computer-represented objects related to said secret;
    - (i) at least one of said objects being accessible by an authorized user as a password;
    - (ii) at least another of said objects being stored in a computer-readable wallet accessible to said access control system; and
  - (c) representing said secret as a function of said plurality of objects, using a composition function; and
  - (d) storing, in a computer-readable memory, said composition function:
    - (i) in a manner accessible to said access control system;
    - (ii) so as to be executable to generate a candidate secret using a user-inputted candidate password in conjunction with at least said another object stored in said wallet;
    - (iii) ~~said generated candidate secret not regenerating said secret~~ generating a bogus secret to camouflage said secret if said candidate password is not said password; and
    - (iv) ~~said generated candidate secret~~ regenerating said secret if said candidate password is said password;
- thereby protecting said secret against unauthorized access by persons not having said password.

Claim 40. (original) The computer-readable medium of claim 39 where:

- (a) said secret represents linkage information among nodes of a network;
- (b) said object accessible by an authorized user is a first graph representing at least a portion of said linkage information; and

- (c) said object stored in said wallet is a second graph representing at least a portion of said linkage information; and
- (d) said composition function accepts as operands at least said first and second graphs.

Claim 41. (original) The computer-readable medium of claim 39 where:

- (a) said secret represents at least one possible state of a system expressible as a Boolean logic function;
- (b) said object accessible by an authorized user is a first matrix representing at least one of said states of said Boolean function;
- (c) said object stored in said wallet is a second matrix representing at least one of said states of said Boolean function; and
- (d) said composition function accepts as operands at least said first and second matrices.

Claim 42. (currently amended) A computer-readable medium containing logic instructions for operating an access control system to release a secret camouflaged to be accessible to an authorized user yet protected against unauthorized access, said logic instructions when executed:

- (a) accessing a plurality of computer-represented objects related to a secret;
  - (i) at least one of said objects being accessible by an authorized user as a password;
  - (ii) at least another of said objects being stored in a computer-readable wallet accessible to said access control system; and
- (b) accessing a composition function representing said secret as a function of said plurality of objects;
- (c) receiving a candidate password inputted by a user;
- (d) generating a candidate secret for said user by executing said composition function using as operands thereto said candidate password in conjunction with at least said another object stored in said wallet;

(i) ~~said generated candidate secret not regenerating said secret~~  
generating a bogus secret configured to camouflage said secret if said candidate password is not  
said password;

(ii) ~~said generated candidate secret~~ regenerating said secret if said  
candidate password is said password; and

(e) outputting said candidate secret to said user of said access control system.

Claim 43. (original) The computer-readable medium of claim 42 where:

(a) said secret represents linkage information among nodes of a network;  
(b) said object accessible by an authorized user is a first graph representing at  
least a portion of said linkage information;

(c) said object stored in said wallet is a second graph representing at least a  
portion of said linkage information; and

(d) said composition function accepts as operands at least said first and  
second graphs.

Claim 44. (original) The computer-readable medium of claim 42 where:

(a) said secret represents at least one possible state of a system expressible as  
a Boolean logic function;

(b) said object accessible by an authorized user is a first array representing at  
least one of said states of said Boolean function; and

(c) said object stored in said wallet is a second array representing at least  
another of said states of said Boolean function; and

(d) said composition function accepts as operands at least said first and  
second arrays.

Claim 45. (currently amended) A computer-readable medium containing logic  
instructions for operating an access control system to protect state information against  
unauthorized access, said logic instructions when executed:

(a) obtaining state information represented in digital form;

- (b) deriving from said state information a first matrix;
  - (c) storing said first matrix as a password usable by an authorized user;
  - (d) deriving from said state information a second matrix;
  - (e) storing said second matrix in a computer-readable wallet accessible to said access control system; and
  - (f) storing, in a computer-readable memory, a composition function executable to generate a candidate matrix using a user-inputted candidate password in conjunction with said second matrix;
    - (i) ~~said generated candidate matrix not regenerating said state information~~ generating a bogus matrix configured to camouflage the matrix if said candidate password is not said password; and
    - (ii) ~~said generated candidate matrix~~ regenerating said state information if said candidate password is said password;
- thereby protecting said state information against unauthorized access by persons not having said password.

Claim 46. (original) The computer-readable medium of claim 45 where said state information includes a graph representing the status of a network characterized by nodes and links among at least some of said nodes.

Claim 47. (original) The computer-readable medium of claim 45 where said state information comprises at least an array including a plurality of output values of a Boolean function, each output value corresponding to a unique sequence of input values for operands of said Boolean function.

Claim 48. (currently amended) A computer-readable medium containing logic instructions for operating an access control system to protect state information against unauthorized access, said logic instructions when executed:

- (a) retrieving a first matrix related to said state information from a computer-readable wallet accessible to said access control system;

- (b) accessing a composition function representing said state information as a function of said first matrix and a password stored as a second matrix;
- (c) receiving a candidate password inputted by a user;
- (d) generating candidate state information for said user by executing said composition function using as operands thereto said candidate password in conjunction with at least said first matrix stored in said wallet;
- (i) ~~said generated candidate state information not regenerating said state information~~ generating said bogus state information configured to camouflage said state information if said candidate password is not said password;
- (ii) ~~said generated candidate state information~~ regenerating said state information if said candidate password is said password; and
- (e) outputting said candidate state information to said user of said access control system.

Claim 49. (original) The computer-readable medium of claim 48 where said state information includes a graph representing the status of a network characterized by nodes and links among at least some of said nodes.

Claim 50. (original) The computer-readable medium of claim 48 where said state information comprises at least an array including a plurality of output values of a Boolean function, each output value corresponding to a unique sequence of input values for operands of said Boolean function.

Claim 51. (currently amended) An access control server configured to camouflage a secret so as to be accessible by an authorized user yet protected against unauthorized access, comprising:

- (a) a computer processor;
- (b) an interface configured to receive in digital form a secret to be protected against unauthorized access;

- (c) a memory configured to store a plurality of computer-represented objects related to said secret;
  - (i) at least one of said objects being accessible by an authorized user as a password;
  - (ii) at least another of said objects being stored in a computer-readable wallet accessible to said access control system; and
- (d) a memory configured to store a composition function representing said secret as a function of said plurality of objects:
  - (i) in a manner accessible to said access control system;
  - (ii) so as to be executable by said processor to generate a candidate secret using a user-inputted candidate password in conjunction with at least said another object stored in said wallet;
  - (iii) said generated candidate secret not regenerating said secret if said candidate password is not said password; and
  - (iv) said generated candidate secret regenerating said secret if said candidate password is said password;thereby protecting said secret against unauthorized access by persons not having said password.

Claim 52. (currently amended) An access control server to release a secret camouflaged to be accessible to an authorized user yet protected against unauthorized access, comprising:

- (a) a memory configured to store a plurality of computer-represented objects related to a secret;
  - (i) at least one of said objects being accessible by an authorized user as a password;
  - (ii) at least another of said objects being stored in a computer-readable wallet accessible to said access control server; and

- (b) a memory configured to store a composition function representing said secret as a function of said plurality of objects;
- (c) an interface configured to receive a candidate password inputted by a user;
- (d) a computer processor configured to execute said composition function to generate a candidate secret for said user by using as operands thereto said candidate password in conjunction with at least said another object stored in said wallet;
  - (i) ~~said generated candidate secret not regenerating said secret~~ generating bogus secret configured to camouflage said secret if said candidate password is not said password;
  - (ii) ~~said generated candidate secret~~ regenerating said secret if said candidate password is said password; and
- (e) an interface configured to output said candidate secret to said user of said access control server.

Claim 53. (currently amended) An access control server to protect state information against unauthorized access, comprising:

- (a) a computer processor;
- (b) an interface configured to obtain state information represented in digital form;
- (c) a decomposition module configured to decompose said state information into at least a first matrix and a second matrix;
- (d) a memory configured to store said first matrix as a password usable by an authorized user;
- (e) a memory configured to store said second matrix in a computer-readable wallet accessible to said access control server; and
- (f) a memory configured to store a composition function executable by said processor to generate a candidate matrix using a user-inputted candidate password in conjunction with said second matrix;

(i) ~~said generated candidate matrix not regenerating said state information~~ generating bogus state information to camouflage said state information if said candidate password is not said password; and

(ii) ~~said generated candidate matrix~~ regenerating said state information if said candidate password is said password;

thereby camouflaging said state information to protecting said state information against unauthorized access by persons not having said password.

Claim 54. (currently amended) An access control server to protect state information against unauthorized access, comprising:

(a) a computer-readable wallet configured to store a first matrix related to said state information accessible to said access control server;

(b) a memory configured to store a composition function representing said state information as a function of said first matrix and a password stored as a second matrix;

(c) an interface configured to receive a candidate password inputted by a user;

(d) a computer processor configured to execute said composition function to generate candidate state information for said user by using as operands to said composition function said candidate password in conjunction with at least said first matrix stored in said wallet;

(i) ~~said generated candidate state information not regenerating said state information~~ generating bogus state information to camouflage said state information if said candidate password is not said password;

(ii) ~~said generated candidate state information~~ regenerating said state information if said candidate password is said password; and

(e) an interface configured to output said candidate state information to said user of said access control server.

Claim 55. (currently amended) An access control system to camouflage a secret so as to be accessible by an authorized user yet protected against unauthorized access, comprising:



(a) means for representing in digital form a secret to be protected against unauthorized access;

(b) means for storing a plurality of computer-represented objects related to said secret;

(i) at least one of said objects being accessible by an authorized user as a password;

(ii) at least another of said objects being stored in a computer-readable wallet accessible to said access control system; and

(c) means for representing said secret as a function of said plurality of objects, using a composition function; and

(d) means for storing, in a computer-readable memory, said composition function:

(i) in a manner accessible to said access control system;

(ii) so as to be executable to generate a candidate secret using a user-inputted candidate password in conjunction with at least said another object stored in said wallet;

(iii) ~~said generated candidate secret not regenerating said secret~~ generating a bogus secret configured to camouflage said secret if said candidate password is not said password; and

(iv) ~~said generated candidate secret~~ regenerating said secret if said candidate password is said password;

thereby camouflaging said secret to protecting said secret against unauthorized access by persons not having said password.

Claim 56. (currently amended) An access control system releasing a secret camouflaged to be accessible to an authorized user yet protecting against unauthorized access, said method comprising the steps of:

(a) means for accessing a plurality of computer-represented objects related to a secret;

(i) at least one of said objects being accessible by an authorized user as a password;

(ii) at least another of said objects being stored in a computer-readable wallet accessible to said access control system; and

(e)(b) means for accessing a composition function representing said secret as a function of said objects;

(d)(c) means for receiving a candidate password inputted by a user;

(e)(d) means for generating a candidate secret for said user by executing said composition function using as operands thereto said candidate password in conjunction with at least said another object stored in said wallet;

(i) ~~said generated candidate secret not regenerating said secret~~  
generating a bogus secret configured to camouflage said secret if said candidate password is not said password;

(ii) ~~said generated candidate secret~~ regenerating said secret if said candidate password is said password; and

(f)(e) means for outputting said candidate secret to said user of said access control system.

Claim 57. (currently amended) An access control system to protect state information against unauthorized access, comprising:

(a) means for obtaining state information represented in digital form;  
(b) means for deriving from said state information a first matrix;  
(c) means for storing said first matrix as a password usable by an authorized user;  
(d) means for deriving from said state information a second matrix;  
(e) means for storing said second matrix in a computer-readable wallet accessible to said access control system; and

(f) means for storing, in a computer-readable memory, a composition function executable to generate a candidate matrix using a user-inputted candidate password in conjunction with said second matrix;

(i) ~~said generated candidate matrix not regenerating said state information~~ generating bogus state information configured to camouflage said state information if said candidate password is not said password; and

(ii) ~~said generated candidate matrix~~ regenerating said state information if said candidate password is said password;

thereby camouflaging said state information to protecting said state information against unauthorized access by persons not having said password.

Claim 58. (currently amended) An access control system to protect state information against unauthorized access, comprising:

(a) means for retrieving a first matrix related to said state information from a computer-readable wallet accessible to said access control system;

(b) means for accessing a composition function representing said state information as a function of said first matrix and a password stored as a second matrix;

(c) means for receiving a candidate password inputted by a user;

(d) means for generating candidate state information for said user by executing said composition function using as operands thereto said candidate password in conjunction with at least said first matrix stored in said wallet;

(i) ~~said generated candidate state information not regenerating said state information~~ generating bogus state information configured to camouflage said state information if said candidate password is not said password;

(ii) ~~said generated candidate state information~~ regenerating said state information if said candidate password is said password; and

(e) means for outputting said candidate state information to said user of said access control system.

Claim 59. (currently amended) A method for operating an access control system to protect a secret against unauthorized access, said method comprising the steps of:

(a) obtaining a secret in digital form;

(b) modeling said secret as a graph;

- (c) camouflaging said secret by decomposing said graph into:
  - (i) a first sub-graph to be distributed as a password to an authorized user of said system; and
  - (ii) a second sub-graph to be stored in a manner accessible to said system;
  - (iii) by relating said first and second sub-graphs to said graph via a composition function configured to regenerate said secret using a user-inputted candidate password in conjunction with said second sub-graph ~~only~~ when said candidate password is said password and generate a bogus secret to camouflage said secret when said candidate password is not said password; and
- (d) storing said camouflaged secret for subsequent access by a user; thereby camouflaging ~~protecting~~ said secret against unauthorized access by persons not having said password.

Claim 60. (currently amended) A method for operating an access control system to protect a secret against unauthorized access, said method comprising the steps of:

- (a) obtaining a secret in digital form;
- (b) modeling said secret as a matrix representing at least a portion of a truth table corresponding to a Boolean function;
- (c) camouflaging said secret by decomposing said matrix into:
  - (i) a first portion to be distributed as a password to an authorized user of said system; and
  - (ii) a second portion to be stored in a manner accessible to said system;
  - (iii) by relating said first and second portions to said matrix via a composition function configured to regenerate said secret using a user-inputted candidate password in conjunction with said second portion ~~only~~ when said candidate password is said password and generate a bogus secret to camouflage said secret when said candidate password is not said password; and
- (d) storing said camouflaged secret for subsequent access by a user;

thereby camouflaging ~~protecting~~ said secret against unauthorized access by persons not having said password.

Claim 61. (currently amended) A method for operating an access control system to protect a secret against unauthorized access, said method comprising the steps of:

- (a) retrieving, from a computer-readable wallet, a first sub-graph:
  - (i) related to a secret camouflaged as a graph by said system; and
  - (ii) accessible to an authorized user as a password;
- (b) accessing a composition function representing said secret as a function of said first sub-graph and a stored second sub-graph accessible to said system;
- (c) receiving a candidate password inputted by a user;
- (d) generating a candidate secret for said user by executing said composition function using as operands thereto said candidate password in conjunction with at least said first sub-graph;
  - (i) ~~said generated candidate secret not regenerating said secret~~  
generating a bogus secret in lieu of said secret to camouflage said secret if said candidate password is not said password;
  - (ii) ~~said generated candidate secret~~ regenerating said secret if said candidate password is said password; and
- (e) outputting said candidate secret to said user of said access control system.

Claim 62. (currently amended) A method for operating an access control system to protect a secret against unauthorized access, said method comprising the steps of:

- (a) retrieving, from a computer-readable wallet, a first matrix:
  - (i) related to a secret camouflaged as a Boolean function by said system; and
  - (ii) accessible to an authorized user as a password;
- (b) accessing a composition function representing said secret as a function of said first matrix and a stored second matrix accessible to said system;
- (c) receiving a candidate password inputted by a user;

(d) generating a candidate secret for said user by executing said composition function using as operands thereto said candidate password in conjunction with at least said first matrix;

(i) ~~said-generated candidate secret not regenerating said secret~~  
generating a bogus secret configured to camouflage said secret if said candidate password is not said password;

(ii) ~~said-generated candidate secret~~ regenerating said secret if said candidate password is said password; and

(e) outputting said candidate secret to said user of said access control system.

Claim 63. (currently amended) A computer-readable medium containing logic instructions for operating an access control system to protect a secret against unauthorized access, said logic instructions when executed:

(a) obtaining a secret in digital form;

(b) modeling said secret as a graph;

(c) camouflaging said secret by decomposing said graph into:

(i) a first sub-graph to be distributed as a password to an authorized user of said system; and

(ii) a second sub-graph to be stored in a manner accessible to said system;

(iii) by relating said first and second sub-graphs to said graph via a composition function configured to regenerate said secret using a user-inputted candidate password in conjunction with said second sub-graph ~~only~~ when said candidate password is said password and generating a bogus secret to camouflage said secret when said candidate password is not said password; and

(d) storing said camouflaged secret for subsequent access by a user;  
thereby camouflaging ~~protecting~~ said secret against unauthorized access by persons not having said password.

Claim 64. (currently amended) A computer-readable medium containing logic instructions for operating an access control system to protect a secret against unauthorized access, said logic instructions when executed:

- (a) obtaining a secret in digital form;
- (b) modeling said secret as a matrix representing at least a portion of a truth table corresponding to a Boolean function;
- (c) camouflaging said secret by decomposing said matrix into:
  - (i) a first portion to be distributed as a password to an authorized user of said system; and
  - (ii) a second portion to be stored in a manner accessible to said system;
  - (iii) by relating said first and second portions to said matrix via a composition function configured to regenerate said secret using a user-inputted candidate password in conjunction with said second portion ~~only~~ when said candidate password is said password and generating a bogus secret to camouflage said secret when said candidate password is not said password; and
- (d) storing said camouflaged secret for subsequent access by a user; thereby camouflaging ~~protecting~~ said secret against unauthorized access by persons not having said password.

Claim 65. (currently amended) A computer-readable medium containing logic instructions for operating an access control system to protect a secret against unauthorized access, said logic instructions when executed:

- (a) retrieving, from a computer-readable wallet, a first sub-graph:
  - (i) related to a secret camouflaged as a graph by said system; and
  - (ii) accessible to an authorized user as a password;
- (b) accessing a composition function representing said secret as a function of said first sub-graph and a stored second sub-graph accessible to said system;
- (c) receiving a candidate password inputted by a user;

(d) generating a candidate secret for said user by executing said composition function using as operands thereto said candidate password in conjunction with at least said first sub-graph;

(i) ~~said-generated candidate secret not regenerating said secret~~  
generating a bogus secret configured to camouflage said secret if said candidate password is not said password;

(ii) ~~said-generated candidate secret~~ regenerating said secret if said candidate password is said password; and

(e) outputting said candidate secret to said user of said access control system.

Claim 66. (currently amended) A computer-readable medium containing logic instructions for operating an access control system to protect a secret against unauthorized access, said logic instructions when executed:

(a) retrieving, from a computer-readable wallet, a first matrix:

(i) related to a secret camouflaged as a Boolean function by said system; and

(ii) accessible to an authorized user as a password;

(b) accessing a composition function representing said secret as a function of said first matrix and a stored second matrix accessible to said system;

(c) receiving a candidate password inputted by a user;

(d) generating a candidate secret for said user by executing said composition function using as operands thereto said candidate password in conjunction with at least said first matrix;

(i) ~~said-generated candidate secret not regenerating said secret~~  
generating a bogus secret configured to camouflage said secret if said candidate password is not said password;

(ii) ~~said-generated candidate secret~~ regenerating said secret if said candidate password is said password; and

(e) outputting said candidate secret to said user of said access control system.